



Volume fume extraction

# Zero Smog EL Kit 1

Fume extraction unit with flexible arm and funnel nozzle

120 VA

WT compatible

LOW SOUND LEVEL



< 53 db(A)

Order No. FT91 01 269 9

- Fume extraction unit for 1 to 2 workplaces.
- Fine dust pre-filter M5 that can be separately changed, without having to change main filter
- Active carbon foam for effective gas filtering
- Portable fume extraction unit, for placement under or next to the bench-top.
- Easy filter change.



## TECHNICAL DATA

Max. capacity	1-2 workplaces
Dimensions W x D x H (inch)	13.19 x 14.17 x 17.52
Dimensions W x D x H (mm)	335 x 360 x 445
Weight (ca) in kg	8.6
Voltage	220-240 V (50/60 Hz)
Heating output	120 VA
Noise level (distance 1 m) dB(A)	< 53
Max Turbine Vacuum (Pa)	2500
Capacity m <sup>3</sup> /h	150
Pre filter	Pre-filter mat class M5
Compact filter	Particle filter H13, Active carbon filter

Scope of supply	Order No.	Model	Description
		Zero Smog EL Unit	Zero Smog EL Unit
	OF15	OF15 Flexible extraction arm	Extraction arm, flexible, Ø 60 mm for sloped and funnel nozzles, length 1,5 m
	ALFA	ALFA Funnel Nozzle	Easy- Click 60 Funnel nozzle , for flexible and stativ extraction arm, width 230 mm, height 100 mm. To be mounted on an aluminium extraction arm without flexible hose, adapter Z is needed. See extraction arms accessories.
	T005 87 627 01	Filterset H13 for Zero Smog 2, Zero Smog EL, WFE 2ES / CS	Filterset H13 for Zero Smog 2, Zero Smog EL, WFE 2ES / CS
	T005 87 628 46	Fixing clamp	Fixing clamps Ø 63mm, 1 piece, for fixing 60mm extraction arms