

Proheat® Varitemp® Heat Gun, Kit & Accessories

Rugged variable temperature heat gun

- New 230 Volt CE Certified model available with four cordset options
- Compact, lightweight, easy-to-use
- Balanced ergonomic design prevents operator fatigue
- Variable temperature 130°F to 840°F (54°C to 449°C)
- Patented electronic closed loop temperature control system maintains constant temperature and protects unit from overheating
- Base provides built-in stand for hands-free use
- Protective hand/switch guard and hanging loop
- UL Listed or CE Certified, Made in USA
- Use to heat temperature sensitive materials including specialty connectors, solder preforms, shrink tubing and more



PH-1200
PH-2200

USA
MADE IN



35016

35017

35026

35216

35292

35293

35294

35351



Easy access variable temperature control



PH-1200-1
PH-2200-1

Complete heat shrink system



PH-1200K
PH-2200K

Proheat Varitemp with rugged storage case and all 5 specialty attachments

MODEL NO.	DESCRIPTION
PH-1200	130° F to 840° F 54°C to 449° C 15 CFM 120V 60 Hz 11A 1300W cUL _{US}
PH-1200-1	130° F to 840° F 54°C to 449° C 15 CFM 120V 60 Hz 11A 1300W cUL _{US} with bench stand (35216) and specialty connector attachment (35292)
PH-1200K	130° F to 840° F 54°C to 449° C 15 CFM 120V 60 Hz 11A 1300W cUL _{US} with storage case and all 5 attachments, (35309)
PH-2200	130° F to 840° F 54°C to 449° C 16 CFM 230V 50/60 Hz 6.2A 1410W CE
PH-2200-1	130° F to 840° F 54°C to 449° C 16 CFM 230V 50/60 Hz 6.2A 1410W CE with bench stand (35216) and specialty connector attachment (35292)
PH-2200K	130° F to 840° F 54°C to 449° C 16 CFM 230V 50/60 Hz 6.2A 1410W CE with storage case and all 5 attachments (35309)




Replacement Heating Element with thermo couple
120V 35031
220V 35032

NOTE: Users should independently evaluate the suitability of the product for their application.

See Optional Accessories on page 8

Specifications

- Air Velocity: 3584 FPM (PH-1200), 4000 (PH-2200)
- Motor: Permanent Magnet
- Nozzle Opening: .88" I.D., 1.31" O.D.
- Cordset: 6 ft., 3-wire grounded
- Dimensions: 8.2" L x 3.0" W x 7.3" H
- Tool Net Weight: 1.6 lbs.
- Shipping Weight Tool: 2 lbs.
- Shipping Weight Kit: 7 lbs.



Dry Materials



Shrink Wrap