








## PURSWAB® ESD APPLICATORS

These applicators are designed for working in and around the most static-sensitive components and parts. A range of shapes, sizes, and materials let you find a swab made specifically for each of your applications.



FEATURED SWAB: # 3605 ESD

	Item No.	Item Description	Packaging pack, weight	Handle length x diameter	Tip length x diameter	Full Length
	1273-PF ESD	Safe for static-sensitive components. Both paddle foam tip and solid polypropylene handle are static-dissipative. Tip is thermally bonded to handle. Use dry or with IPA or DI water.	20/50, 2 lbs	66.675 x 2.286 mm 2.625 x 0.09"	14.224 x 3.962 mm 0.56 x 0.156"	67.462 mm 2.656"
	1283-PF ESD	Precision pointed tip made of reticulated 100 PPI foam thermally bonded to a solid static-dissipative handle. Use dry or with IPA and DI water.	20/50, 1 lb	68.58 x 2.54 mm 2.7 x 0.1"	19.989 x 3.505 mm 0.787 x 0.138"	69.215 mm 2.725"
	1621-PF ESD	Precision pointed tip made of reticulated 100 PPI foam thermally bonded to a solid static-dissipative handle. Use dry or with IPA and DI water.	20/50, 2 lbs	81.534 x 2.54 mm 3.21 x 0.1"	10.922 x 3.556 mm 0.43 x 0.14"	82.804 mm 3.26"
	1806-PF ESD	Standard shape, safe for static-sensitive components. Both foam tip and solid polypropylene handle are static-dissipative. Tip is adhered to handle with thermoplastic adhesive. Use dry or with IPA or DI water.	20/50, 3 lbs	149.225 x 2.54 mm 5.875 x 0.1"	15.875 x 4.775 mm 0.625 x 0.188 "	152.4 mm 6"
	3605 ESD	Safe for static-sensitive components. Microfiber tip ultrasonically welded to static-dissipative polypropylene handle. Excellent wipe-dry characteristics.	10/100, 3 lbs	149.225 x 2.54 mm 5.875 x 0.1"	16.129 x 5.996 mm 0.635 x 0.236"	152.4 mm 6"
	3676 ESD	Safe for static-sensitive components. Polyester knit tip ultrasonically welded to solid static-dissipative handle. Excellent wipe-dry characteristics.	20/50, 3 lbs	150.418 x 3.048 mm 5.922 x 0.12"	16.789 x 6.807 mm 0.661 x 0.268"	152.857 mm 6.018"
	3677 ESD	Superior wipe-dry characteristics. Ultra-clean microfiber paddle tip ultrasonically welded to solid, static-dissipative Stat-Rite® polypropylene handle. Use dry or with IPA, DI water, or solvents.	10/100, 3 lbs	150.418 x 3.048 mm 5.922 x 0.12"	16.789 x 6.807 mm 0.661 x 0.268"	152.4 mm 6"