

TorqueFix® and Torque cable key.



2850 TorqueFix® torque screwdriver.
 With a fixed torque value pre-set by Wiha.
Automatic release.

- Handle: Ergonomic multi-component handle, particularly light and compact. Handle sizes proportioned to optimise torque setting. Audible and perceptible click when the pre-set torque has been attained. Compatible with all blades of the 2859 series.
- Standards: EN ISO 6798, BS EN 26789, ASME B107.14M.
- Accuracy: ±6%, traceable to national standards.
- Application: For applications where recommended torque settings are important. Use in combination with a Wiha torque interchangeable blade.
- Extra: Delivered in practical plastic box, incl. factory calibration certificate.
- Note: The below articles are available from stock. Further articles with pre-set, customer torque values of between 0.15 and 8 Nm are available on request. Bit holders or blades are not included in delivery.
- Individual: Products can be designed individually using the configurator at mytorque.wiha.com. (Can be chosen freely: text field, torque unit, torque value)

Order-No.	Nm	±%	⊙	↔	↕	≡
26925	0.4	6%	4	112	23	1
26127	0.5	6%	4	112	23	1
26047	0.6	6%	4	112	23	1
26327	0.8	6%	4	112	23	1
26048	0.9	6%	4	112	23	1
26133	1.1	6%	4	119	30	1
26049	1.2	6%	4	119	30	1
26901	1.5	6%	4	119	30	1
26051	2.0	6%	4	119	30	1
26128	2.5	6%	4	119	30	1
26052	3.0	6%	4	126	36	1
26129	3.8	6%	4	126	36	1
26053	5.0	6%	4	132	41	1
26130	5.5	6%	4	132	41	1
34533	6.0	6%	4	132	41	1
26131	7.2	6%	4	132	41	1



2850 S2 Torque cable key set for circular plug connectors.
 For Wiha torque screwdrivers.

- Handle: TorqueFix® torque screwdrivers. Ergonomic multi-component handle, particularly light and compact.
- Material: Robust, glass-fibre reinforced plastic combines the high quality hexagonal stainless steel insert with the blade tang of chrome-vanadium-molybdenum steel.
- Application: For controlled fastening of circular plug connectors with hexagonal head according to specified torque.

Order-No.	Nm	⊙	mm	↔	↕	≡	
36846	0.4	9	230	78	112	23	1
36847	0.6	13	230	78	112	23	1
36848	1.5	22	240	90	119	30	1

easyTorque.



292 easyTorque torque screwdriver.
 With a fixed torque value ex-factory.

- Handle: Multi-component handle optimally designed for the hand enables optimal power transmission. Audible and perceptible click when the pre-set torque has been attained. Rapid identification with imprint on handle end. Unlimited loosening torque. Mechanism insensitive to industrial lubricants. Compatible with all blades of the 2859 series.
- Accuracy: ±10%
- Application: For applications where recommended torque settings are important. Use in combination with a Wiha torque interchangeable blade.
- Note: Bit holders or blades are not included in delivery.

Order-No.	Nm	±%	⊙	↔	↕	≡
36229	0.5	10%	4	130	34	1
36230	0.6	10%	4	130	34	1
36240	0.9	10%	4	130	34	1
36231	1.1	10%	4	130	34	1
36233	1.2	10%	4	130	34	1
36234	1.4	10%	4	130	34	1
36235	2.0	10%	4	130	34	1
36236	2.5	10%	4	130	34	1
36237	3.0	10%	4	130	34	1
36238	3.8	10%	4	130	34	1
36320	4.0	10%	4	130	34	1
36321	4.5	10%	4	130	34	1
36239	5.0	10%	4	130	34	1

Wiha torque screwdrivers.

Torque interchangeable blades.



2859 Torque slotted interchangeable blade. For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.
Wiha ChromTop® finish on tip for a perfect fit every time.
Colour-coding: grey.

Standards: Blade tip DIN ISO 2380-1.

Application: For applications where recommended torque settings are important.

Order-No.	⊖	⊕	⦿	↔	↔	max. Nm	⊞
26227	0.25	1.5	4	175	42	0.15	10
26228	0.4	2.0	4	175	42	0.4	10
26151	0.4	2.5	4	175	42	0.4	10
26277	0.5	3.0	4	175	42	0.6	10
26278	0.6	3.5	4	175	42	1.1	10
26279	0.8	4.0	4	175	42	2.5	10



2859 Torque Phillips interchangeable blade. For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.
Wiha ChromTop® finish on tip for a perfect fit every time.
Colour-coding: dark blue.

Standards: Blade tip DIN ISO 8764-1.

Application: For applications where recommended torque settings are important.

Order-No.	⊕	⦿	↔	↔	max. Nm	⊞
26199	PH000	4	175	42	0.4	10
26196	PH00	4	175	42	0.4	10
26197	PH0	4	175	42	0.9	10
26058	PH1	4	175	42	3.8	10
27079	PH2	4	175	42	5.5	10



2859 Torque cable key for circular plug connectors. For Wiha torque screwdrivers.

Material: Robust, glass-fibre reinforced plastic combines the high quality hexagonal stainless steel insert with the blade tang of chrome-vanadium-molybdenum steel.

Application: For controlled fastening of circular plug connectors with hexagonal head according to specified torque.

Order-No.	⦿	⦿	↔	↔	max. Nm	⊞
36414	8	4	78	218	1	10
36415	9	4	78	218	1	10
38004	11	4	78	218	1.5 NEW	10
36413	1/2"	4	78	218	1.5	10
36416	12	4	78	218	1.5	10
36417	13	4	78	218	1.5	10
36418	14	4	78	218	1.5	10
36419	17	4	78	218	1.5	10
36421	18	4	78	218	1.5	5
36553	19	4	78	218	1.5	5
36422	22	4	90	233	2	5
36423	24	4	90	233	2	5

Torque interchangeable blades.



2859 Torque Pozidriv interchangeable blade. For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.
Wiha ChromTop® finish on tip for a perfect fit every time.
Colour-coding: light blue.

Standards: Blade tip DIN ISO 8764-1.

Application: For applications where recommended torque settings are important.

Order-No.	⊕	⦿	↔	↔	max. Nm	⊞
26198	PZ0	4	175	42	0.9	10
26148	PZ1	4	175	42	3.8	10
26889	PZ2	4	175	42	5.5	10



2859 Torque hex interchangeable blade. For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.
Wiha ChromTop® finish on tip for a perfect fit every time.
Colour-coding: red.

Application: For applications where recommended torque settings are important.

Order-No.	⦿	⦿	↔	↔	max. Nm	⊞
26544	1.3	4	175	42	0.4	10
26200	1.5	4	175	42	0.9	10
26060	2.0	4	175	42	1.8	10
26061	2.5	4	175	42	3.8	10
26062	3.0	4	175	42	5.5	10
26063	4.0	4	175	42	8.0	10



2859 Torque ball end hex interchangeable blade. For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.
Wiha ChromTop® finish on tip for a perfect fit every time.
Colour-coding: red.

Application: For applications where recommended torque settings are important.
Extra: The ball end enables the user to work at angles up to 25°.

Order-No.	⦿	⦿	↔	↔	max. Nm	⊞
26221	1.5	4	175	42	0.4	10
26222	2.0	4	175	42	0.9	10
26223	2.5	4	175	42	2.0	10
26224	3.0	4	175	42	3.8	10
26225	4.0	4	175	42	8.0	10

Torque interchangeable blades.



2859 Torque TORX® interchangeable blade.
For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.
Wiha ChromTop® finish on tip for a perfect fit every time.
Colour-coding: dark green.

Application: For applications where recommended torque settings are important.
Extra: Very slim blade diameter for hard-to-reach screws.

Order-No.	●	●	↔	↔	max. Nm	↔
30852	T4	4	175	42	0.25	10
26158	T5	4	175	42	0.4	10
26064	T6	4	175	42	0.6	10
26065	T7	4	175	42	0.9	10
26066	T8	4	175	42	1.3	10
26059	T9	4	175	42	2.5	10
26067	T10	4	175	42	3.7	10
26068	T15	4	175	42	5.5	10
26069	T20	4	175	42	8.0	10
26070	T25	4	175	42	8.0	10

Torque interchangeable blades.



2859 Torque TORX PLUS® interchangeable blade.
For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.
Wiha ChromTop® finish on tip for a perfect fit every time.
Colour-coding: light green.

Application: For applications where recommended torque settings are important.
Extra: Very slim blade diameter for hard-to-reach screws.

Order-No.	●	●	↔	↔	max. Nm	↔
26159	5IP	4	175	42	0.5	10
26071	6IP	4	175	42	0.8	10
26152	7IP	4	175	42	1.3	10
26072	8IP	4	175	42	2.0	10
26154	9IP	4	175	42	3.0	10
26155	10IP	4	175	42	4.5	10
26073	15IP	4	175	42	6.6	10
26156	20IP	4	175	42	8.0	10
26157	25IP	4	175	42	8.0	10



2859 Torque TORX® MagicSpring® interchangeable blade.
For Wiha torque screwdrivers.
Retaining spring holds TORX® screws in place.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.
Wiha ChromTop® finish on tip for a perfect fit every time.
Colour-coding: dark green.

Application: For applications where recommended torque settings are important.
Extra: Very slim blade diameter for hard-to-reach screws.

Order-No.	●	●	↔	↔	max. Nm	↔
27818	T6	4	175	42	0.6	10
27812	T7	4	175	42	0.9	10
27813	T8	4	175	42	1.3	10
27814	T9	4	175	42	2.5	10
27815	T10	4	175	42	3.8	10
27816	T15	4	175	42	5.5	10
27817	T20	4	175	42	8.0	10
29467	T25	4	175	42	8.0	10



2859 Torque TORX PLUS® MagicSpring® interchangeable blade.
For Wiha torque screwdrivers.
Retaining spring holds TORX PLUS® screws in place.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.
Wiha ChromTop® finish on tip for a perfect fit every time.
Colour-coding: light green.

Application: For applications where recommended torque settings are important.
Extra: Very slim blade diameter for hard-to-reach screws.

Order-No.	●	●	↔	↔	max. Nm	↔
29553	6IP	4	175	42	0.8	10
29554	7IP	4	175	42	1.3	10
29555	8IP	4	175	42	2.0	10
29556	9IP	4	175	42	3.0	10
29557	10IP	4	175	42	4.5	10
29558	15IP	4	175	42	6.6	10
29559	20IP	4	175	42	8.0	10
29560	25IP	4	175	42	8.0	10



2859 Torque bit universal holder.
For Wiha torque screwdrivers.
Suitable for C 6.3 and E 6.3 (1/4") bits.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Sleeve: Made of stainless steel, black-plastic coated.

Application: For applications where recommended torque settings are important.

Order-No.	○	●	↔	↔	↔
27526	1/4	4	162	11	10



2859 Torque adapter blade.
For Wiha torque screwdrivers.
Suitable for 1/4" square sockets.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Head: Nickel-plated, spring-mounted ball.

Application: For applications where recommended torque settings are important.

Order-No.	●	●	↔	↔	↔
26229	1/4	4	155		10