

# Wiha torque screwdrivers.

## TorqueVario®-S with scale.



### 2852 TorqueVario®-S Torque screwdriver.

Torque value can be set via window scale.  
Automatic release.

- Handle: Torque infinitely adjustable with Torque-Setter setting tool (also supplied).  
Ergonomic multi-component handle, particularly light and compact.  
Handle sizes proportioned to optimise torque setting.  
Audible and perceptible click when the pre-set torque has been attained.  
Compatible with all blades of the 2859 series.
- Standards: EN ISO 6798, BS EN 26789, ASME B107.14M.
- Accuracy: ±6%, tracing to national standards (see table for other tolerances).
- Application: For applications where recommended torque settings are important.  
Use in combination with a Wiha torque interchangeable blade.
- Extra: Delivered in practical plastic box.  
Incl. works inspection protocol.
- Note: Bit holders or blades are not included in delivery.
- Individual: Products can be designed individually using the configurator at [mytorque.wiha.com](http://mytorque.wiha.com).  
(Can be chosen freely: text field, torque unit)

Order-No.	Nm	±%	⊗	↔	↓	📦
36849	0.04-0.46•	10%	4	127	23	1
26888	0.1-0.6	10%	4	127	23	1
36850	0.1-0.6	6%	4	127	23	1
26461	0.4-1.0	6%	4	127	23	1
26462	0.8-2.0	6%	4	131	30	1
26463	1.0-5.0	6%	4	138	36	1
26464	2.0-8.0	6%	4	142	41	1

• Precision in range of 0.1-0.46 Nm



### 285-900 Torque-Setter.

Setting tool for variable torque screwdrivers.  
Included in every torque screwdriver delivery.

- Blade: Octagonal blade, through hardened, zinc-plated.
- Supplement: Included in every torque screwdriver delivery.

Order-No.	↔	↔	📦
26864	150	80	1

## TorqueVario®-S sets.



### 2852 S10 TorqueVario®-S Torque screwdriver set, 13 pcs.

- Torque value can be set via window scale.  
With bit universal holder and 10 Phillips/ Pozidriv/ TORX®/ hex Standard bits.
- Handle: Model 1.0-5.0 Nm.  
Torque infinitely adjustable with Torque-Setter setting tool (also supplied).  
Ergonomic multi-component handle, particularly light and compact.  
Audible and perceptible click when the pre-set torque has been attained.
- Standards: EN ISO 6798, BS EN 26789, ASME B107.14M.
- Accuracy: ±6%, traceable to national standards.
- Application: For applications where recommended torque settings are important.  
Supply in robust box.
- Extra: Incl. works inspection protocol.

Order-No.	Series	📦
26893	2852 S10	1
	2852	TorqueVario®-S, model 1.0-5.0 Nm
	2859	Torque bit universal holder
	285-900	Torque-Setter
⊕	7011 Z	PH1x25 PH2x25
⊕	7012 Z	PZ1x25 PZ2x25
⊕	7015 Z	T10x25 T15x25 T20x25 T25x25
⊙	7013 Z	3.0x25 4.0x25



### 2852 S10-01 TorqueVario®-S Torque screwdriver set, 13 pcs.

- Torque value can be set via window scale.  
With bit universal holder and 10 TORX®/ TORX PLUS® Standard bits especially for applications with indexable cutter inserts.

Order-No.	Series	📦
34614	2852 S10-01	1
	2852	TorqueVario®-S, model 1.0-5.0 Nm
	2859	Torque bit universal holder
	285-900	Torque-Setter
⊕	7015 Z	T7x25 T8x25 T9x25 T10x25
⊕	7016 Z	T15x25 T15x25
⊙	7016 Z	7IPx25 8IPx25 9IPx25 10IPx25 15IPx25

# Wiha torque screwdrivers.

## Torque interchangeable blades.



### 2859 Torque slotted interchangeable blade. For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.  
Wiha ChromTop® finish on tip for a perfect fit every time.  
Colour-coding: grey.

Standards: Blade tip DIN ISO 2380-1.

Application: For applications where recommended torque settings are important.

Order-No.	⊖	⊕	⦿	↔	↔	max. Nm	⊖
26227	0.25	1.5	4	175	42	0.15	10
26228	0.4	2.0	4	175	42	0.4	10
26151	0.4	2.5	4	175	42	0.4	10
26277	0.5	3.0	4	175	42	0.6	10
26278	0.6	3.5	4	175	42	1.1	10
26279	0.8	4.0	4	175	42	2.5	10



### 2859 Torque Phillips interchangeable blade. For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.  
Wiha ChromTop® finish on tip for a perfect fit every time.  
Colour-coding: dark blue.

Standards: Blade tip DIN ISO 8764-1.

Application: For applications where recommended torque settings are important.

Order-No.	⊕	⦿	↔	↔	max. Nm	⊖
26199	PH000	4	175	42	0.4	10
26196	PH00	4	175	42	0.4	10
26197	PH0	4	175	42	0.9	10
26058	PH1	4	175	42	3.8	10
27079	PH2	4	175	42	5.5	10



### 2859 Torque cable key for circular plug connectors. For Wiha torque screwdrivers.

Material: Robust, glass-fibre reinforced plastic combines the high quality hexagonal stainless steel insert with the blade tang of chrome-vanadium-molybdenum steel.

Application: For controlled fastening of circular plug connectors with hexagonal head according to specified torque.

Order-No.	⦿	⦿	↔	↔	max. Nm	⊖
36414	8	4	78	218	1	10
36415	9	4	78	218	1	10
38004	11	4	78	218	1.5 NEW	10
36413	1/2"	4	78	218	1.5	10
36416	12	4	78	218	1.5	10
36417	13	4	78	218	1.5	10
36418	14	4	78	218	1.5	10
36419	17	4	78	218	1.5	10
36421	18	4	78	218	1.5	5
36553	19	4	78	218	1.5	5
36422	22	4	90	233	2	5
36423	24	4	90	233	2	5

## Torque interchangeable blades.



### 2859 Torque Pozidriv interchangeable blade. For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.  
Wiha ChromTop® finish on tip for a perfect fit every time.  
Colour-coding: light blue.

Standards: Blade tip DIN ISO 8764-1.

Application: For applications where recommended torque settings are important.

Order-No.	⊕	⦿	↔	↔	max. Nm	⊖
26198	PZ0	4	175	42	0.9	10
26148	PZ1	4	175	42	3.8	10
26889	PZ2	4	175	42	5.5	10



### 2859 Torque hex interchangeable blade. For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.  
Wiha ChromTop® finish on tip for a perfect fit every time.  
Colour-coding: red.

Application: For applications where recommended torque settings are important.

Order-No.	⦿	⦿	↔	↔	max. Nm	⊖
26544	1.3	4	175	42	0.4	10
26200	1.5	4	175	42	0.9	10
26060	2.0	4	175	42	1.8	10
26061	2.5	4	175	42	3.8	10
26062	3.0	4	175	42	5.5	10
26063	4.0	4	175	42	8.0	10



### 2859 Torque ball end hex interchangeable blade. For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.  
Wiha ChromTop® finish on tip for a perfect fit every time.  
Colour-coding: red.

Application: For applications where recommended torque settings are important.  
Extra: The ball end enables the user to work at angles up to 25°.

Order-No.	⦿	⦿	↔	↔	max. Nm	⊖
26221	1.5	4	175	42	0.4	10
26222	2.0	4	175	42	0.9	10
26223	2.5	4	175	42	2.0	10
26224	3.0	4	175	42	3.8	10
26225	4.0	4	175	42	8.0	10

**Torque interchangeable blades.**



**2859** Torque TORX® interchangeable blade.  
For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.  
Wiha ChromTop® finish on tip for a perfect fit every time.  
Colour-coding: dark green.

Application: For applications where recommended torque settings are important.  
Extra: Very slim blade diameter for hard-to-reach screws.

Order-No.	●	●	↔	↔	max. Nm	↔
30852	T4	4	175	42	0.25	10
26158	T5	4	175	42	0.4	10
26064	T6	4	175	42	0.6	10
26065	T7	4	175	42	0.9	10
26066	T8	4	175	42	1.3	10
26059	T9	4	175	42	2.5	10
26067	T10	4	175	42	3.7	10
26068	T15	4	175	42	5.5	10
26069	T20	4	175	42	8.0	10
26070	T25	4	175	42	8.0	10

**Torque interchangeable blades.**



**2859** Torque TORX PLUS® interchangeable blade.  
For Wiha torque screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.  
Wiha ChromTop® finish on tip for a perfect fit every time.  
Colour-coding: light green.

Application: For applications where recommended torque settings are important.  
Extra: Very slim blade diameter for hard-to-reach screws.

Order-No.	●	●	↔	↔	max. Nm	↔
26159	5IP	4	175	42	0.5	10
26071	6IP	4	175	42	0.8	10
26152	7IP	4	175	42	1.3	10
26072	8IP	4	175	42	2.0	10
26154	9IP	4	175	42	3.0	10
26155	10IP	4	175	42	4.5	10
26073	15IP	4	175	42	6.6	10
26156	20IP	4	175	42	8.0	10
26157	25IP	4	175	42	8.0	10



**2859** Torque TORX® MagicSpring® interchangeable blade.  
For Wiha torque screwdrivers.  
Retaining spring holds TORX® screws in place.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.  
Wiha ChromTop® finish on tip for a perfect fit every time.  
Colour-coding: dark green.

Application: For applications where recommended torque settings are important.  
Extra: Very slim blade diameter for hard-to-reach screws.

Order-No.	●	●	↔	↔	max. Nm	↔
27818	T6	4	175	42	0.6	10
27812	T7	4	175	42	0.9	10
27813	T8	4	175	42	1.3	10
27814	T9	4	175	42	2.5	10
27815	T10	4	175	42	3.8	10
27816	T15	4	175	42	5.5	10
27817	T20	4	175	42	8.0	10
29467	T25	4	175	42	8.0	10



**2859** Torque TORX PLUS® MagicSpring® interchangeable blade.  
For Wiha torque screwdrivers.  
Retaining spring holds TORX PLUS® screws in place.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.  
Wiha ChromTop® finish on tip for a perfect fit every time.  
Colour-coding: light green.

Application: For applications where recommended torque settings are important.  
Extra: Very slim blade diameter for hard-to-reach screws.

Order-No.	●	●	↔	↔	max. Nm	↔
29553	6IP	4	175	42	0.8	10
29554	7IP	4	175	42	1.3	10
29555	8IP	4	175	42	2.0	10
29556	9IP	4	175	42	3.0	10
29557	10IP	4	175	42	4.5	10
29558	15IP	4	175	42	6.6	10
29559	20IP	4	175	42	8.0	10
29560	25IP	4	175	42	8.0	10



**2859** Torque bit universal holder.  
For Wiha torque screwdrivers.  
Suitable for C 6.3 and E 6.3 (1/4") bits.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Sleeve: Made of stainless steel, black-plastic coated.

Application: For applications where recommended torque settings are important.

Order-No.	○	●	↔	↔	↔
27526	1/4	4	162	11	10



**2859** Torque adapter blade.  
For Wiha torque screwdrivers.  
Suitable for 1/4" square sockets.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, chrome-plated.

Head: Nickel-plated, spring-mounted ball.

Application: For applications where recommended torque settings are important.

Order-No.	●	●	↔	↔	↔
26229	1/4	4	155		10