

Screw extractor set



Hexagon with spiral drill bit 8-pcs.

405 11

Order-No.		
03988	10	
●	2,0 / 2,5 / 3,0 / 4 / 5 / 6 / 8 / 10	

Screw extractor



Order-No.	●	↔	●	
03847	2,0	85	6,0	10
03848	2,5	85	6,0	10
03849	3,0	85	7,0	10
03850	4	85	8,0	10
03851	5	85	8,0	10
03852	6	95	8,0	10
03853	8	95	10,0	10
03854	10	110	12,0	10

Screwdriver set SoftFinish® ESD



Slotted, Phillips 5-pcs.

302ESD HK5 01

Order-No.		
27252	1	
⊖	3,0 x 100 / 4,0 x 100	
⊕	PH0 x 60 / PH1 x 80 / PH2 x 100	
IEC 61340-5-1.		

TORX® 5-pcs.

362ESD K5

Order-No.		
27253	1	
⊕	T6 x 60 / T8 x 60 / T9 x 60 / T10 x 80 / T15 x 80	
IEC 61340-5-1.		

INFOBOX:  
Electrostatic  
conductive ESD  
tools



Sensitive, electronic components can be damaged even at a very low voltage.

- Dissipative tools by Wiha discharge the electrostatic energy in a controlled, safe manner.
- ESD tools meet the ESD Standard IEC 61340-5-1.
- ESD tool handles have a surface resistance of  $10^9$  -  $10^9$  Ohm.

## Screwdriver set Precision ESD



### Slotted, Phillips 6-pcs.

272 K6

Order-No.							
08463							1
⊖	1,5 x 40 / 2,0 x 40 / 2,5 x 50 / 3,0 x 50						
⊕	PH00 x 40 / PH0 x 50						
IEC 61340-5-1.							

### TORX® 6-pcs.

278 K6

Order-No.							
26919							1
⊕	T5 x 40 / T6 x 40 / T7 x 40 / T8 x 40 / T10 x 50 / T15 x 60						
IEC 61340-5-1.							

### Hexagon 6-pcs.

275 K6

Order-No.							
32278							1
⦿	0,9 x 40 / 1,3 x 40 / 1,5 x 50 / 2 x 50 / 2,5 x 60 / 3 x 60						
IEC 61340-5-1.							

### Hexagon nut driver 6-pcs.

277 K6

Order-No.							
32279							1
⦿	2,5 x 60 / 3 x 60 / 3,5 x 60 / 4 x 60 / 5 x 60 / 5,5 x 60						
IEC 61340-5-1.							

## Screwdriver SoftFinish® ESD



### ⊖ Slotted

302ESD

Order-No.	⊖	⊖	⦿	⦿	⊕	⊕	⊕
08179	2,5	75	0,4	2,5	179	23	10
27150	3,0	100	0,5	3,0	204	23	10
27151	4,0	100	0,8	4,0	211	30	10
08182	5,5	125	1,0	5,5	236	30	10
08183	6,5	150	1,2	6,0	268	36	10
IEC 61340-5-1.							

### ⊕ Phillips

311ESD

Order-No.	⊕	⦿	⦿	⊕	⊕	⊕	
08184	PH0	60	3,0	164	23	10	
08185	PH1	80	4,5	191	30	10	
08186	PH2	100	6,0	218	36	10	
IEC 61340-5-1.							

### ⊕ Pozidriv

313ESD

Order-No.	⊕	⦿	⦿	⊕	⊕	⊕	
26928	PZ0	60	3,0	164	23	10	
26929	PZ1	80	4,5	191	30	10	
IEC 61340-5-1.							

### ⊕ TORX®

362ESD

Order-No.	⊕	⦿	⦿	⊕	⊕	⊕	
31432	T3	60	2,5	164	23	10	
27148	T4	60	2,5	164	23	10	
27641	T5	60	3,5	164	23	10	
27149	T6	60	3,5	164	23	10	
31901	T7	60	3,5	164	23	10	
22436	T8	60	3,5	164	23	10	
27145	T9	60	4,0	171	30	10	
27144	T10	80	4,0	191	30	10	
27146	T15	80	4,0	191	30	10	
27147	T20	100	4,0	218	36	10	
IEC 61340-5-1.							

## Screwdriver SoftFinish® ESD



### Slotted Stubby

302ESD

Order-No.	⊖	↔	⊖:	●:	↔	+	▬
32151	4,0	25	0,8	4,0	81	34	10
32152	5,5	25	1,0	5,5	81	34	10
32153	6,5	25	1,2	6,5	81	34	10

IEC 61340-5-1.

### Phillips Stubby

311ESD

Order-No.	⊕	↔	●:	↔	+	▬
32154	PH1	25	4,5	81	34	10
32155	PH2	25	6,0	81	34	10

IEC 61340-5-1.

### Pozidriv Stubby

313ESD

Order-No.	⊕	↔	●:	↔	+	▬
32156	PZ1	25	4,5	81	34	10
32157	PZ2	25	6,0	81	34	10

IEC 61340-5-1.

## Screwdriver Precision ESD



### Slotted

272

Order-No.	⊖	↔	⊖:	●:	↔	+	▬
07634	1,5	40	0,25	2,0	120	12,5	10
07635	2,0	40	0,40	2,0	120	12,5	10
07636	2,5	50	0,40	2,5	145	13,0	10
07637	3,0	50	0,50	3,0	145	13,0	10
07638	3,5	60	0,60	3,5	170	14,0	10
07639	4,0	60	0,80	4,0	170	14,0	10

IEC 61340-5-1.

### Phillips

273

Order-No.	⊕	↔	●:	↔	+	▬
28053	PH000	40	2,0	120	12,5	10
07640	PH00	40	2,0	120	12,5	10
07641	PH0	50	3,0	145	13,0	10
07642	PH1	60	4,0	170	14,0	10

IEC 61340-5-1.

### Pozidriv

274

Order-No.	⊕	↔	●:	↔	+	▬
07643	PZ1	60	4,0	170	14	10

IEC 61340-5-1.

### TORX® MagicSpring®

278R

Order-No.	⊕	↔	●:	↔	+	▬
27748	T6	40	2,5	120	12,5	10
27749	T7	40	2,5	120	12,5	10
27759	T8	40	2,5	120	12,5	10
27750	T9	50	3,0	145	13,0	10
27751	T10	50	3,0	145	13,0	10
27752	T15	60	3,5	170	14,0	10

IEC 61340-5-1.

### TORX®

278

Order-No.	⊕	↔	●:	↔	+	▬
25676	T1	40	2,5	120	12,5	10
25677	T2	40	2,5	120	12,5	10
21256	T3	40	2,5	120	12,5	10
21255	T4	40	2,5	120	12,5	10
07659	T5	40	2,5	120	12,5	10
07660	T6	40	2,5	120	12,5	10
07661	T7	40	2,5	120	12,5	10
07662	T8	40	2,5	120	12,5	10
07663	T9	50	3,0	145	13,0	10
07664	T10	50	3,0	145	13,0	10
07665	T15	60	3,5	170	14,0	10
07666	T20	60	4,0	170	14,0	10

IEC 61340-5-1.

### TORX PLUS®

278IP

Order-No.	⊕	↔	●:	↔	+	▬
28198	4IP	40	2,5	120	12,5	10
27761	5IP	40	2,5	120	12,5	10
27762	6IP	40	2,5	120	12,5	10
27763	7IP	40	2,5	120	12,5	10
27764	8IP	40	2,5	120	12,5	10
27765	9IP	50	3,0	145	13,0	10
27766	10IP	50	3,0	145	13,0	10
27767	15IP	60	3,5	170	14,0	10

IEC 61340-5-1.

### Ball end hex

276

Order-No.	●	↔	↔	+	▬
07649	1,5	50	145	13,0	10
07650	2	50	145	13,0	10
07651	2,5	60	170	14,0	10
07652	3	60	170	14,0	10

IEC 61340-5-1.

● Hex

275

Order-No.	⊙	↔	↔	↔	↔	↔
27707	0,7	40	120	12,5		10
27708	0,9	40	120	12,5		10
07644	1,3	40	120	12,5		10
07645	1,5	50	145	13,0		10
07646	2	50	145	13,0		10
07647	2,5	60	170	14,0		10
07648	3	60	170	14,0		10
32315	4	60	170	14,0		10

IEC 61340-5-1.

Precision ESD lifter



279-10

Order-No.	↔	↔	↔	↔	↔
07667	3,5	50	145	13,0	5

IEC 61340-5-1.

○ Hex nut driver

277

Order-No.	○	↔	↔	↔	↔	↔	↔
32312	1,5	60	2,5	-	155	13,0	10
32313	2,0	60	2,9	-	155	13,0	10
07653	2,5	60	4,0	4,0	155	13,0	10
07654	3	60	5,0	5,0	155	13,0	10
07655	3,5	60	5,3	6,0	155	13,0	10
07656	4	60	5,5	6,0	155	13,0	10
32314	4,5	60	6,2	7,0	155	13,0	10
07657	5	60	6,8	7,0	155	13,0	10
07658	5,5	60	7,6	8,0	170	14,0	10

IEC 61340-5-1.

**Torque screwdriver set TorqueVario®-S ESD**



**assorted, variably adjustable torque limit, 13-pcs. in box**

**2882 S10**

Order-No.	
27687	1

- Torque screwdriver TorqueVario®-S ESD variably settable torque limit / 0,5 - 2,0 Nm
  - Bit holder clamping with ball for torque screwdriver with long handle
  - Adjusting tool for torque screwdriver with long handle
  - ⊖ 4,5 x 25 / 5,5 x 25
  - ⊕ PH0 x 25 / PH1 x 25
  - ⊕ PZ0 x 25 / PZ1 x 25
  - ⊕ T7 x 25 / T8 x 25 / T9 x 25 / T10 x 25
- IEC 61340-5-1. DIN EN ISO 6789.

**Torque screwdriver TorqueVario®-S ESD**



**○ variably settable torque limit**

**2882**

Order-No.	Nm	±%	⊖	⊕	⊕	⊕
36851	0,04-0,46	10%	4	127	23	1
26865	0,1-0,6	10%	4	127	23	1
36852	0,1-0,6	6%	4	127	23	1
26629	0,4-1,0	6%	4	127	23	1
26866	0,5-2,0	6%	4	131	30	1
30495	0,8-5,0	6%	4	138	36	1

• Precision in range of 0.1-0.46 Nm IEC 61340-5-1. DIN EN ISO 6789.

**INFOBOX:  
Electrostatic  
conductive ESD  
tools**



**Sensitive, electronic components can be damaged even at a very low voltage.**

- Dissipative tools by Wiha discharge the electrostatic energy in a controlled, safe manner.
- ESD tools meet the ESD Standard IEC 61340-5-1.
- ESD tool handles have a surface resistance of 10<sup>9</sup> -10<sup>9</sup> Ohm.

Screwdriver with interchangeable blade set SYSTEM 4 ESD



assorted 11-pcs.

2691 T11 ESD

Order-No.	
31499	5

	Screwdriver handle SoftFinish®-telescopic ESD for SYSTEM 4 interchangeable blade
	1,5 - 0,25 / 2,0 - 0,4 / 2,5 - 0,4
	PH000 - PH00 / PH0 - PH1
	T6 - T8 / T7 - T9
	1,5 - 1,5 • / 2 - 2 • / 2,5 - 2,5 •
• With ball end	

Screwdriver handle SoftFinish®-telescopic



for SYSTEM 4 interchangeable blade

2691

Order-No.					
30373	4,0	105	23		10

Screwdriver handle SoftFinish®-telescopic ESD



for SYSTEM 4 interchangeable blade

2691ESD

Order-No.					
31498	4,0	105	23		10
IEC 61340-5-1.					

## Interchangeable blade SYSTEM 4



### Slotted

269

Order-No.	⊖	⊖	⊖	⊖	↔	⬡	▬
00576	1,5	0,25	3,0	0,5	120	4,0	5
00577	2,0	0,4	3,5	0,6	120	4,0	5
00578	2,5	0,4	4,0	0,8	120	4,0	5

### Slotted/ Phillips

269

Order-No.	⊖	⊖	⊕	↔	⬡	▬
00601	2,0	0,4	PH00	120	4,0	5
00602	3,0	0,5	PH0	120	4,0	5
00603	4,0	0,8	PH1	120	4,0	5

### Phillips

269

Order-No.	⊕	⊕	↔	⬡	▬
00579	PH000	PH00	120	4,0	5
00580	PH0	PH1	120	4,0	5

### Pozidriv

269

Order-No.	⊕	⊕	↔	⬡	▬
03186	PZ0	PZ1	120	4,0	5

### TORX®

269

Order-No.	⬢	⬢	↔	⬡	▬
26122	T1	T2	120	4,0	5
26123	T3	T4	120	4,0	5
26124	T5	T6	120	4,0	5
00597	T6	T8	120	4,0	5
00598	T7	T9	120	4,0	5
00599	T10	T15	120	4,0	5
00600	T15	T20	120	4,0	5

### Ball end hex

269

Order-No.	●	●	↔	⬡	▬
00582	1,3 •	1,3	120	4,0	5
00583	1,5 •	1,5	120	4,0	5
00584	2 •	2	120	4,0	5
00585	2,5 •	2,5	120	4,0	5
00586	3 •	3	120	4,0	5
00587	4 •	4	120	4,0	5

• With ball end

### Hex

269

Order-No.	○	○	↔	⬡	▬
00588	1,5	1,8	125	4,0	5
00589	2	2,5	125	4,0	5
00590	3	-	125	4,0	5
00591	3,2	-	125	4,0	5
00592	3,5	-	125	4,0	5
00593	4	-	125	4,0	5
00594	4,5	-	125	4,0	5
00595	5	-	125	4,0	5
00596	5,5	-	125	4,0	5

### Reversible screwdriver



### Slotted, Phillips

198-1

Order-No.	⊖	⊕	⬡	↔	▬	⬢	▬
00328	6,0	PH2	6	160	90	22	10



Screwdriver with interchangeable blade set SYSTEM 6



assorted 6-pcs.

281 T6

Order-No. 1  
27715

- Screwdriver handle SoftFinish®-telescopic for SYSTEM 6 interchangeable blade
  - ⊖ ⊖ 3,5 - 4,5 / 4,0 - 6,0 / 5,5 - 6,5
  - ⊕ ⊕ PH1 - PH2
  - ● 5 - 5 •
- With ball end

assorted 6-pcs.

281 T6 01

Order-No. 1  
32298

- Screwdriver handle SoftFinish®-telescopic for SYSTEM 6 interchangeable blade
- ⊖ ⊖ 4,0 - 6,0
- ⊕ ⊕ PH1 - PH2
- ⊗ ⊗ PZ1 - PZ2
- ⊛ ⊛ T10 - T15 / T20 - T25

INFOBOX:  
**Electrostatic  
conductive ESD  
tools**



**Sensitive, electronic components can be damaged even at a very low voltage.**

- Dissipative tools by Wiha discharge the electrostatic energy in a controlled, safe manner.
- ESD tools meet the ESD Standard IEC 61340-5-1.
- ESD tool handles have a surface resistance of  $10^6 - 10^9$  Ohm.

Screwdriver with interchangeable blade set SYSTEM 6



Hexagon nut driver 8-pcs.

U106 T8

Order-No. 1  
27712

- Screwdriver handle SoftFinish®-telescopic for SYSTEM 6 interchangeable blade
- 5,0 - 150 / 5,5 - 150 / 6,0 - 150 / 7,0 - 150 / 8,0 - 150 / 10,0 - 150 / 13,0 - 150

Screwdriver with interchangeable blade set SYSTEM 6 ESD



assorted 6-pcs.

284ESD T6 01

Order-No. 1  
31497

- Screwdriver handle SoftFinish®-telescopic ESD for SYSTEM 6 interchangeable blade
  - ⊖ ⊖ 3,5 - 4,5 / 4,0 - 6,0 / 5,5 - 6,5
  - ⊕ ⊕ PH1 - PH2
  - ● 5 - 5 •
- With ball end



Screwdriver handle SoftFinish®-telescopic



○ for SYSTEM 6 interchangeable blade

284

Order-No.	○	⇄	⚡	▬
30372	6,0	120	36	5

○ for SYSTEM 6 interchangeable blade in blister pack

SB 284

Order-No.	○	⇄	⚡	▬
30404	6,0	120	36	5

Screwdriver handle SoftFinish®-telescopic ESD




○ for SYSTEM 6 interchangeable blade

284ESD

Order-No.	○	⇄	⚡	▬
31496	6,0	120	36	5

IEC 61340-5-1.

Interchangeable blade SYSTEM 6



⊖ Slotted

284

Order-No.	⊖	⊖:	⊖	⊖:	⇄	⬢	▬
27627	3,5	0,6	4,5	0,8	150	6,0	5
00629	4,0	0,8	6,0	1,0	150	6,0	5
00630	5,5	1,0	6,5	1,2	150	6,0	5
36084	8,0	1,2	-	-	150	6,0	5

⊖ Slotted, Phillips

284

Order-No.	⊖	⊖:	⊕	⇄	⬢	▬
00665	4,0	0,8	PH1	150	6,0	5
00666	6,0	1,0	PH2	150	6,0	5
00667	6,5	1,2	PH3	150	6,0	5

⊕ Phillips

284

Order-No.	⊕	⊕	⇄	⬢	▬
00631	PH1	PH2	150	6,0	5
27628	PH2	PH3	150	6,0	5

⊕ Pozidriv

284

Order-No.	⊕	⊕	⇄	⬢	▬
00632	PZ1	PZ2	150	6,0	5
27629	PZ2	PZ3	150	6,0	5

⊕ TORX®

284

Order-No.	⊕	⊕	⇄	⬢	▬
00654	T6	T8	150	6,0	5
00655	T7	T9	150	6,0	5
00656	T10	T15	150	6,0	5
00657	T20	T25	150	6,0	5
00658	T30	T40	150	6,0	5

⊕ TORX® Tamper Resistant (with hole)

284

Order-No.	⊕	⊕	⇄	⬢	▬
27630	T6H	T8H	150	6,0	5
27631	T7H	T9H	150	6,0	5
27632	T10H	T15H	150	6,0	5
27633	T20H	T25H	150	6,0	5
27634	T30H	T40H	150	6,0	5

**Torq-Set®**

284

Order-No.					
27635	TS2	TS4	150	6.0	5
27636	TS6	TS8	150	6.0	5

**Interchangeable blade SYSTEM 6**



**Tri-Wing® 1/4"**

284

Order-No.					
27637	TW0	TW1	150	6.0	5
27638	TW2	TW3	150	6.0	5
27639	TW4	TW5	150	6.0	5

**1/4" square adapter for nut driver inserts**

7803

Order-No.					
03883	1/4	150	6,0		5

**Interchangeable blade SYSTEM 6**



**Extension SYSTEM 6**



**Hex nut driver**

U 106

Order-No.				
08900	4,0	150	6,0	1
08901	4,5	150	6,0	1
08902	5,0	150	6,0	1
08903	5,5	150	6,0	1
08904	6,0	150	6,0	1
08905	7,0	150	6,0	1
08906	8,0	150	6,0	1
08907	9,0	150	6,0	1
08908	10,0	150	6,0	1
08909	11,0	150	6,0	1
08911	13,0	150	6,0	1

**U**

U109 00

Order-No.					
08921	6,0	150	6,0	11	5

**Bit holder SYSTEM 6 clamping with ball**



**U**

7802

Order-No.					
03882	1/4	150	6,0	10	5







Pliers set Professional ESD



**Diagonal cutters, oblique end cutting nippers, needle nose pliers 4-pcs.**

Z 99 0 001 04

Order-No.	
33507	1
	Diagonal cutters Professional ESD wide, pointed head without bevelled edge 115 mm, 4 1/2" (26821)
	Diagonal cutters Professional ESD wide, semi-rounded head with bevelled edge 115 mm, 4 1/2" (26831)
	Oblique end cutting nippers Professional ESD narrow head, approx. 40° with small bevelled edge 110 mm, 4 1/4" (26838)
	Needle nose pliers Professional ESD straight 120 mm, 4 3/4" (26799)

SMD tweezer set Professional ESD




**assorted 4-pcs.**

ZP 99 0 140 02

Order-No.	
32349	1
	Universal tweezers Professional ESD Type AA 130 mm, AA (32318)
	Precision tweezers Professional ESD Type PSF 130 mm, PSF (32325)
	SMD tweezers Professional ESD Type 13 120 mm, 13 (32340)
	SMD tweezers Professional ESD Type 59 117 mm, 59 (32344)

**INFOBOX:  
Electrostatic  
conductive ESD  
tools**



**Sensitive, electronic components can be damaged even at a very low voltage.**

- Dissipative tools by Wiha discharge the electrostatic energy in a controlled, safe manner.
- ESD tools meet the ESD Standard IEC 61340-5-1.
- ESD tool handles have a surface resistance of 10<sup>6</sup> -10<sup>9</sup> Ohm.

Diagonal cutters Professional ESD



narrow, pointed head with bevelled edge

Z 40 1 04

Order-No.	mm	II	✂	Ømm	SB	
26808	115	4 ½	7	0.6		5
27442	115	4 ½	7	0.6	x	5

DIN ISO 9654. IEC 61340-5-1.

Diagonal cutters Professional ESD



wide, pointed head with bevelled edge

Z 41 1 04

Order-No.	mm	II	✂	Ømm	SB	
26816	115	4 ½	7	1		5
27444	115	4 ½	7	1	x	5

DIN ISO 9654. IEC 61340-5-1.

Diagonal cutters Professional ESD



narrow, pointed head without bevelled edge

Z 40 3 04

Order-No.	mm	II	✂	Ømm	
33521	115	4 ½	2	1	5

DIN ISO 9654. IEC 61340-5-1.

Diagonal cutters Professional ESD



wide, pointed head without bevelled edge

Z 41 3 04

Order-No.	mm	II	✂	Ømm	SB	
26821	115	4 ½	2	1		5
27445	115	4 ½	2	1	x	5

DIN ISO 9654. IEC 61340-5-1.

Diagonal cutters Professional ESD



narrow, pointed head with small bevelled edge

Z 40 4 04

Order-No.	mm	II	✂	Ømm	SB	
26814	115	4 ½	2	1		5
27443	115	4 ½	2	1	x	5

DIN ISO 9654. IEC 61340-5-1.

Diagonal cutters Professional ESD



wide, pointed head and wire trapping spring with small bevelled edge

Z 41 4 04

Order-No.	mm	II	✂	Ømm	SB	
26822	115	4 ½	2	1.2		5
27446	115	4 ½	2	1.2	x	5

DIN ISO 9654. IEC 61340-5-1.



**Diagonal cutters Professional ESD**



**narrow, semi-rounded head with small bevelled edge**

**Z 43 1 04**

Order-No.	mm	II	✂	Ømm	SB	SB
26826	115	4 ½	2	1.2		5
27447	115	4 ½	2	1.2	x	5

DIN ISO 9654. IEC 61340-5-1.

**Oblique end cutting nippers Professional ESD**



**wide head, approx. 29° with small bevelled edge**

**Z 46 1 04**

Order-No.	mm	II	✂	Ømm	SB	SB
26835	115	4 ½	2	1.2		5
27450	115	4 ½	2	1.2	x	5

DIN ISO 9654. IEC 61340-5-1.

**Diagonal cutters Professional ESD**



**wide, semi-rounded head with bevelled edge**

**Z 44 1 04**

Order-No.	mm	II	✂	Ømm	SB	SB
26831	115	4 ½	7	1		5
27448	115	4 ½	7	1	x	5

DIN ISO 9654. IEC 61340-5-1.

**Oblique end cutting nippers Professional ESD**



**narrow head, approx. 40° with small bevelled edge**

**Z 46 4 04**

Order-No.	mm	II	✂	Ømm	SB	SB
26838	110	4 ¼	2	0.6		5
27451	110	4 ¼	2	0.6	x	5

DIN ISO 9654. IEC 61340-5-1.

**Diagonal cutters Professional ESD**



**wide, semi-rounded head with small bevelled edge**

**Z 44 3 04**

Order-No.	mm	II	✂	Ømm	SB	SB
26832	115	4 ½	2	1.2		5
27449	115	4 ½	2	1.2	x	5

DIN ISO 9654. IEC 61340-5-1.

**End cutting nippers Professional ESD**



**narrow head with small bevelled edge**

**Z 47 1 04**

Order-No.	mm	II	✂	Ømm	SB	SB
26839	110	4 ¼	2	0.6		5
27452	110	4 ¼	2	0.6	x	5

DIN ISO 9654. IEC 61340-5-1.

### End cutting nippers Professional ESD



#### wide head with small bevelled edge

Z 47 2 04

Order-No.	mm	II	✂	Ømm	SB	
26840	115	4 1/2	2	1.4		5
27453	115	4 1/2	2	1.4	x	5

DIN ISO 9654. IEC 61340-5-1.

### Round-nose pliers Professional ESD



#### Short, rounded jaws

Z 37 0 04

Order-No.	mm	II	SB	
26804	120	4 3/4		5
27440	120	4 3/4	x	5

DIN ISO 9655. IEC 61340-5-1.

### Needle nose pliers Professional ESD



#### straight

Z 36 0 04

Order-No.	mm	II	A	B	D	F	
26799	120	4 3/4	9,5	23	6,5	1,4	5
27329	120	4 3/4	9,5	23	6,5	1,4	5
27905	145	5 3/4	12,0	40	7,5	2,0	5

DIN ISO 9655. IEC 61340-5-1.

### Flat-nose pliers Professional ESD



#### Short, flat jaws

Z 38 0 04

Order-No.	mm	II	SB	
26806	120	4 3/4		5
27441	120	4 3/4	x	5

DIN ISO 9655. IEC 61340-5-1.

### Needle nose pliers Professional ESD



#### curved form, approx. 45°

Z 36 1 04

Order-No.	mm	II	SB	
26802	120	4 3/4		5
27439	120	4 3/4	x	5

DIN ISO 9655. IEC 61340-5-1.

