

Product Information S2333A Wrist Strap/Dual-Footwear Combo Test Kit



S2333A is a Multi-Functional & Precise Test Kit for Wrist Strap & Footwear resistance measurement. Meets and exceeds ANSI/ESD S20.20-2007 (Revision of ANSI/ESD S20.20 1999). NIST Certified.

Features

- Tests Wrist Strap Individually
- Tests One Footwear Individually
- Tests Two-Footwear Simultaneously
- Tests All Three (One Wrist Strap & Two-Footwear) Simultaneously
- The Kit Consists of The Tester, Foldable Foot Plate with attached Connecting Cord (Tester-To-Metal Foot Plate), and a 9V Battery.
- Battery Operated (Can be used worldwide without need for power supply with specific plug configurations).
- Provides Two Connection Points for Wrist Strap Test: a Banana Receptacle & a 3/8" (10mm) Male Snap.
- Color LED Light Indicators
- ON & OFF Sliding Switch

Specifications

Wrist Strap

- Low Fail < 800K Red - High Fai > 35M Red - Pass >800K To <35M Green

Footwear

- Low Fail < 800K Red - High Fai >100M Red - Pass >800K To <100M Green

Low Battery Indicator

Tester Size 6-1/2" L x 3-1/4" x 1-3/8" (65mm x 110mm x 35mm)

14" x 6" (360mm x 150mm)

Red

Tester Net weight 8.35 OZ (236g) **Foot Plate Net Weight** 5 lb (2.30kg)

Metal Foot Plate Sizes (X2)

Foot Plate Size

- **Folded** 15-1/2" x 8" (950mm x 200mm) - **Unfolded (Open)** 15-1/2" x15-3/4' (950mm x 400mm)

Total Kit Package Weight 6 lb 4 OZ (2.9kg)

Total Kit Package Size 17" x 10" x 3" (435mm x 255mm x 80mm)

PI/S2333A/Rev.3/814