



MG 100S

Fume extraction unit MG 100S

100 W

 LOW
SOUND
LEVEL

< 52 db(A)


Order No. 100-10 00- ESD

- Unit purifies air at up to 2 workplaces
- High Gasfilter volume
- Electronic filter control with filter alarm
- Variable speed setting
- Minimized foot print



TECHNICAL DATA

Max. capacity	1-2 workplaces
Dimensions W x D x H (inch)	18, 11 x 8, 26 x 24, 15
Dimensions W x D x H (mm)	460 x 210 x 610
Weight (ca) in kg	15
Voltage	110 - 240 V, 50/60 Hz
Heating output	100 W
Noise level (distance 1 m) dB(A)	< 52
Max Turbine Vacuum (Pa)	2.300
Capacity m ³ /h	140
Pre filter	
Compact filter	Particle filter H13, Wide band gas filter (50 % Active carbon + 50 % Chemisorb)
ESD-safe	✓

Scope of supply	Order No.	Model	Description
		MG 100S Unit	MG 100S Fume Extraction Unit
	100-2000-ESD	Compact filter MG 100S Standard	Particle filter H13 and wide band gas filter, Standard

Volume extraction

Tip extraction

Laser extraction

Accessories volume extraction

Spare filter