



Zero Smog 2

Fume extraction unit Zero Smog 2

185 VA LOW SOUND LEVEL 50 db(A)

Order No. FT91 00 469 9

- Economical unit purifies air up to 2 workplaces
- Easy filter exchange
- Quick and simple installation
- Portable fume extraction unit
- The fume extraction unit Zero Smog 2 is easy to install and operate. It is designed as a small, economical central system for two workplaces. The Zero Smog 2 is available in a beneficial kit.



TECHNICAL DATA

Max. capacity	1-2 workplaces
Dimensions W x D x H (inch)	14,17 x 12,99 x 16,33
Dimensions W x D x H (mm)	360 x 330 x 415
Weight (ca) in kg	9
Voltage	220-240 V (50/60 Hz)
Heating output	185 VA
Noise level (distance 1 m) dB(A)	50
Max Turbine Vacum (Pa)	3.000
Capacity m³/h	190
Pre filter	Pre filter mat class M5
Compact filter	Particle filter H 13, Active carbon filter



Zero Smog 2 Kit 2 Funnel

Fume extraction unit Zero Smog 2 with Kit 2 funnel

185 VA LOW SOUND LEVEL < 53 db(A)

Order No. FT91 00 869 9



Scope of supply	Order No.	Model	Description
		Zero Smog EL Unit	Zero Smog EL Unit
2 x OF15		OF15 Flexible extraction arm	Extraction arm, flexible, Ø 60 mm for sloped and funnel nozzles, length 1,5 m
2 x ALFA		ALFA Funnel Nozzle	Easy- Click 60 Funnel nozzle , for flexible and stativ extraction arm, width 230 mm, height 100 mm. To be mounted on an aluminium extraction arm without flexible hose, adapter Z is needed. See extraction arms accessories.
	FT91004699	Zero Smog 2	Fume extraction unit Zero Smog 2