

# ECO-STAT WRIST-STRAP ELECTRONIC CONTINUOUS MONITORING DEVICE

The device will simultaneously monitor the status of wrist-strap and grounding to determine that no internal breakage has occurred. Otherwise, red LED will light up and trigger audible alarm.



## FEATURES

- easy to use
- no pre-check required
- instant warning of wrist-strap failure
- electronic design
- small and light weight
- low priced
- resistance adjustment capability

## BENEFITS

- highly durable
- increase productivity
- improves quality, tests without having to leave the workstation
- easy and convenient to use
- reliable and effective
- save cost, economical
- allows user to adjust to body resistance between ground path and wrist-strap. Use a flat head screwdriver to set body resistance by turning clockwise when the resistance is high or anti-clockwise when the resistance is low. Green light shows when you are in the correct position.

## SPECIFICATION

**Model:** EMS99-1 (110V) or EMS99-2 (220V)

**BWS-6** replaceable 6' wrist strap

### Operation:

**Red LED** and audible alarm on grounding or Wrist-strap indicates FAIL.

**Green LED** indicates PASS.

Charge Decay Test:

>0.02 seconds <0.09 seconds @±100Vdc to ±10Vdc. All conditioning and testing were performed at 27°C ± 3°C and 65% ± 10% RH for 48 hours.

Input Voltage : 6 VDC

Dimensions : 44(W) x 75(D) x 24(H) mm

Weight : 51g

## STANDARD PACKING

Monitor, wrist-strap, adapter and grounding cord in a box

Box Size : 142(W) x 94(D) x 55(H) mm

Gross Weight : 317g

Net Weight : 254g

Packing : 50 pieces / carton

Gross Weight : 17.0kg

Net Weight : 16.0kg

Carton Dimension : 500(W) x 310(D) x 340(H) mm

For more information, please contact



**Techco (Private) Limited**

10 Admiralty Street #06-75/76/77/78 Northlink Building,

Singapore 757695

Tel: +65 6758 1111

Fax: +65 6758 9007

E-mail: [singapore@techcogroup.com](mailto:singapore@techcogroup.com)

Website: [www.techcogroup.com](http://www.techcogroup.com)