

Torque screwdriver set TorqueVario®-S ESD



assorted, variably adjustable torque limit, 13-pcs. in box

2882 S10

Order-No.	
27687	1

- Torque screwdriver TorqueVario®-S ESD variably settable torque limit / 0,5 - 2,0 Nm
 - Bit holder clamping with ball for torque screwdriver with long handle
 - Adjusting tool for torque screwdriver with long handle
 - ⊖ 4,5 x 25 / 5,5 x 25
 - ⊕ PH0 x 25 / PH1 x 25
 - ⊕ PZ0 x 25 / PZ1 x 25
 - ⊕ T7 x 25 / T8 x 25 / T9 x 25 / T10 x 25
- IEC 61340-5-1. DIN EN ISO 6789.

Torque screwdriver TorqueVario®-S ESD



○ variably settable torque limit

2882

Order-No.	Nm	±%	⊖	⊕	⊕	⊕
36851	0,04-0,46	10%	4	127	23	1
26865	0,1-0,6	10%	4	127	23	1
36852	0,1-0,6	6%	4	127	23	1
26629	0,4-1,0	6%	4	127	23	1
26866	0,5-2,0	6%	4	131	30	1
30495	0,8-5,0	6%	4	138	36	1

• Precision in range of 0.1-0.46 Nm IEC 61340-5-1. DIN EN ISO 6789.

**INFOBOX:
Electrostatic
conductive ESD
tools**



Sensitive, electronic components can be damaged even at a very low voltage.

- Dissipative tools by Wiha discharge the electrostatic energy in a controlled, safe manner.
- ESD tools meet the ESD Standard IEC 61340-5-1.
- ESD tool handles have a surface resistance of 10⁹ -10⁹ Ohm.