

WE 1010

1-Channel Power Unit, digital, 70 W
Product no.: T0053298699



Benefits

- › Power unit, 1 channel with soldering iron WEP 70 and safety rest PH 70
- › 70W solder iron with ergonomic handle and providing toolless tip change
- › ESD safe station, iron and heat-resistant silicon cable for safe handling
- › Using ET soldering tips
- › Standby mode and auto setback conserves energy, protects equipment
- › Password-protected to preserve settings
- › Replacement for 4ETH, 4ETK, 4ETO, 4ETS necessary. For WEP 70 4ETHL, 4ETKL, 4EKOL and 4ETSL must be used.



Technical Data

Dimensions L x W x H (mm)	150 x 120 x 98
Dimensions L x W x H (inches)	5.91 x 4.72 x 3.86
Weight (approx.) in kg	1.4
Voltage	230 V
Power	85 W
Channels	1
Temperature range (depends on tool) °C	100 - 450
Temperature range (depends on tool) °F	200 - 850
Temperature accuracy °C	Average tip temperature can be „offset“ to +/- 5°C at idle with no load
Temperature accuracy °F	Average tip temperature can be „offset“ to +/- 9°F at idle with no load
Temperature stability °C	± 6
Temperature stability °F	± 10
Equipotential bonding socket	---
Display	Digital LC Display
Air consumption l/min	---
Operating pressure in bar/psi	---
Capacity l/min	---
Vacuum	---


ET soldering tips



A = Width mm
B = Thickness mm
C = Length mm

Chisel



Model	A	B	C	PU	Order No.
ET A	1.6	0.7	34.5	1 10 100	4ETA-1 4ETA-10 4ETA-100
					
ET B	2.4	0.8	34.5	1 10	4ETB-1 4ETB-10
					
ET C	3.2	0.8	34.5	1 10 100	4ETC-1 4ETC-10 4ETC-100
					
ET D	4.6	0.8	34.5	1 10	4ETD-1 4ETD-10
					
ET DS SOLDERING TIP 50MM	4.6	0.8	34.5	1	4ETDS-1 4ETDS-10
					
ET E	5.6	1.2	34.5	1 10 100	4ETE-1 4ETE-10 4ETE-100
					

Model	A	B	C	PU	Order No.
ET HL	0.8	0.4	34.5	1	4ETHL
					
ET L	2.0	1.0	43.5	1 10 100	4ETL-1 4ETL-10 4ETL-100
					
ET M	3.2	1.2	43.5	1 10	4ETM-1 4ETM-10
					
ET R	1.6	0.7	34.5	1 10	4ETR-1 4ETR-10
					
ET KL	1.2	0.8	44	1	4ETKL
					
ET SL	0.3		43.5	1	4ETSL
					

Round



Model	A	B	C	PU	Order No.
ET AA SOLDERING TIP 16MM	4.6	0.8	34.5	1	4ETAA-1
					
ET BB	2.4		34.5	1 10	4ETBB-1 4ETBB-10
					
ET CC	3.2		34.5	1 10	4ETCC-1 4ETCC-10
					

Model	A	B	C	PU	Order No.
ET CS	3.2		34.5	1 100	4ETCS-1 4ETCS-100
					
ET F	1.2		34.5	1 10	4ETF-1 4ETF-10
					
ET P	0.8		34.5	1 10	4ETP-1 4ETP-10
					

Conical



Model	A	B	C	PU	Order No.
ET OL	0.8		43.5	1	4ETOL
					

Measuring tip

Model	A	B	C	PU	Order No.
ET Measuring tip	0.5		30	1	T005 24 750 99
					

Gullwing tip



Model	A	B	C	PU	Order No.
ET GW	4.3	3	35	1	T005 41 045 99
					
ET C HPB SOLDERING TIP FE+NI	4.3	3	35	1	T005 41 003 75
					
ET SMD 2,5 x 1,5 mm	2.5	1.5	45	1	T005 41 039 99
					
ET SMD 3,8 x 1,5 mm	3.8	1.5	45	1	T005 41 040 99
					