















RT Pico MS Tips

- RT Pico Soldering Tips for WXPP MS Soldering Irons
- Short tip-to-grip distance for maximum precision
- MIL-SPEC / IPC standard (potential for MS versions)
- Made for the smallest precision soldering applications (Aerospace, Military (only MS versions), Electronics, Sensors, Medical devices, Automotive)
- High performance active tip for the smallest components: 0402 down to 01005










CHISEL						
Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTP 002 S MS		T0050102199	40	16.3	0.2/0.1	Chisel Ø 0.2 × 0.1 mm MIL-SPEC
RTP 002 S NW MS		T0050102299	40	16.3	0.2/0.1	Chisel Ø 0.2 × 0.1 mm, MIL-SPEC, not wettable
RTP 004 S MS		T0050102399	40	16.3	0.4/0.2	Chisel Ø 0.4 × 0.2 mm, MIL-SPEC
RTP 008 S MS		T0050102499	40	16.3	0.8/0.3	Chisel Ø 0.8 × 0.3 mm, MIL-SPEC





CHISEL						
Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTP 010 S MS		T0050102599	40	16.3	1.0/0.3	Chisel Ø 1.0 × 0.3 mm, MIL-SPEC
RTP 013 S MS		T0050102699	40	16.3	1.3/0.3	Chisel Ø 1.3 × 0.3 mm, MIL-SPEC







BEVEL CUT						
Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTP 004 B MS		T0050101999	40	16.3	0.4	Bevel cut Ø 0.4 mm, MIL-SPEC
RTP 012 B MS		T0050102099	40	16.3	1.2	Bevel cut Ø 1.2 mm, MIL-SPEC

CONICAL



Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTP 001 C MS		T0050101399	40	17.9	0.1	Conical Ø 0.1 mm, MIL-SPEC
RTP 001 C NW MS		T0050101499	40	17.9	0.1	Conical Ø 0.1 mm, MIL-SPEC, not wettable
RTP 001 C X MS		T0050101799	40	20.6	0.1	Conical bent 0.1 mm, MIL-SPEC
RTP 002 C MS		T0050101599	40	16.3	0.2	Conical Ø 0.2 mm, MIL-SPEC
RTP 002 C X MS		T0050101899	40	20.6	0.1	Conical bent 0.2 mm, MIL-SPEC
RTP 004 C MS		T0050101699	40	16.3	0.4	Conical Ø 0.4 mm, MIL-SPEC

GULLWING						
Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTP 020 G MS		T0050103099	40	15.9	2.0	Gullwing Ø 2.0 mm, MIL-SPEC

KNIFE						
Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTP 010 K NW MS		T0050102899	40	15.9	1.0/0.2	Knife 1.0 mm, MIL-SPEC, not wettable
RTP 010 K MS		T0050102799	40	15.9	1.0/0.2	Knife 1.0 mm, MIL-SPEC
RTP 025 K MS		T0050102999	40	17.3	2.5/0.3	Knife 2.5 mm, MIL-SPEC