











RT Micro Tips












- RT Micro Soldering Tips for WXMP / WXMP MS Soldering Irons
- High performance active tips for micro and standard components
- Covers the widest range of geometries and sizes
- MIL-SPEC / IPC standard (potential free, MS versions)
- Versatile performance for micro and standard components covering the widest range of applications (Aerospace, Military (only MS versions), Electronics, Sensors, Medical devices, Automotive)




CHISEL						
Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTM 003 S		T0054461270N	40	19.0	0.3/0.15	Chisel Ø 0.3 x 0.15 mm
RTM 003 S NW		T0054462699N	40	20.0	0.3/0.1	Chisel chromed Ø 0.3 x 0.1 mm, not wettable for 0201 / 0204 components
RTM 003 S NW MS		T0054462671N	40	20.0	0.3/0.1	Chisel Ø 0.3 x 0.1 mm, MIL-SPEC, not wettable
RTM 004 S		T0054461299N	40	20.0	0.4/0.15	Chisel Ø 0.4 x 0.15 mm
RTM 004 S MS		T0054461599N	40	20.0	0.4/0.15	Chisel Ø 0.4 x 0.15 mm MIL-SPEC
RTM 006 S MS		T0050100499	40	23.0	0.6/0.4	Chisel Ø 0.6 x 0.4 mm, MIL-SPEC
RTM 008 S X		T0054460599N	40	23.0	0.8/0.4	Chisel 30° bent 0.8 x 0.4 mm









CHISEL




Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTM 008 S X MS		T0054461999N	40	23.0	0.8/0.4	Chisel Ø 0.8 x 0.4 mm, MIL-SPEC
RTM 008 S		T0054460999N	40	23.0	0.8/0.4	Chisel Ø 0.8 x 0.4 mm
RTM 008 S MS		T0054462399N	40	23.0	0.8/0.4	Chisel Ø 0.8 x 0.4 mm, MIL-SPEC
RTM 010 S		T0050100599	40	18.0	1.0/0.3	Chisel Ø 1.0 x 0.3 mm
RTM 010 S MS		T0050100699	40	18.0	1.0/0.3	Chisel Ø 1.0 x 0.3 mm, MIL-SPEC
RTM 013 S		T0054460399N	40	20.0	1.3/0.4	Chisel Ø 1.3 x 0.4 mm
RTM 013 S MS		T0054461699N	40	20.0	1.3/0.4	Chisel Ø 1.3 x 0.4 mm, MIL-SPEC
RTM 013 S X		T0054460371N	40	28.0	1.3/0.5	Chisel, sloped Ø 1.3 x 0.5 mm
RTM 013 S X MS		T0054460373N	40	28.0	1.3/0.5	Chisel, sloped Ø 1.3 x 0.5 mm, MIL-SPEC
RTM 015 S		T0054460499N	40	19.0	1.5/0.4	Chisel Ø 1.5 x 0.4 mm
RTM 015 S MS		T0054461899N	40	19.0	1.5/0.4	Chisel Ø 1.5 x 0.4 mm, MIL-SPEC





CHISEL




Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTM 018 S		T0050100799	40	18.0	1.8/0.4	Chisel Ø 1.8 x 0.4 mm
RTM 018 S MS		T0050100899	40	18.0	1.8/0.4	Chisel Ø 1.8 x 0.4 mm, MIL-SPEC
RTM 022 S		T0054460899N	40	19.0	2.2/0.4	Chisel Ø 2.2 x 0.4 mm
RTM 022 S MS		T0054462299N	40	19.0	2.2/0.4	Chisel Ø 2.2 x 0.4 mm, MIL-SPEC
RTM 032 S		T0050100999	55	17.5	3.2/0.9	Chisel Ø 3.2 x 0.9 mm
RTM 032 S MS		T0050101099	55	17.5	3.2/0.9	Chisel Ø 3.2 x 0.9 mm, MIL-SPEC
RTM 036 S		T0054461199N	40	19.0	3.6/0.9	Chisel Ø 3.6 x 0.9 mm
RTM 036 S MS		T0054463199N	40	19.0	3.6/0.9	Chisel Ø 3.6 x 0.9 mm, MIL-SPEC








BEVEL CUT












Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTM 004 B		T0050100299	40	18.5	0.4	Bevel cut Ø 0.4 mm
RTM 004 B MS		T0050100399	40	18.5	0.4	Bevel cut Ø 0.4 mm, MIL-SPEC
RTM 012 B		T0054460699N	40	19.0	1.2	Round form 45° sloped, Ø 1.2 mm
RTM 012 B MS		T0054462099N	40	19.0	1.2	Round form 45° sloped Ø 1.2 mm, MIL-SPEC







CONICAL




Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTM 001 C NW		T0054462599N	40	20.0	0.1	Conical chromed Ø 0.1 mm, chrome, not wettable for 0201 / 0204 components
RTM 001 C NW MS		T0054462571N	40	20.0	0.1	Conical Ø 0.1 mm, chrome, not wettable, MIL- SPEC
RTM 002 C L		T0050100099	40	18.7	0.2	Conical, Long Ø 0.2 mm
RTM 002 C		T0054460199N	40	20.0	0.2	Conical Ø 0.2 mm
RTM 002 C L MS		T0050100199	40	18.7	0.2	Conical, Long Ø 0.2 mm, MIL-SPEC
RTM 002 C MS		T0054461499N	40	20.0	0.1	Conical Ø 0.2 mm, MIL-SPEC
RTM 004 C X MS		T0054463399N	40	26.5	0.4	Conical Ø 0.4 mm, MIL-SPEC

CONICAL						
Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTM 005 C X MS		T0054463299N	40	25.5	0.5	Conical Ø 0.5 mm, MIL-SPEC
RTM 008 C		T0054460299N	40	19.0	0.8	Conical Ø 0.8 mm
RTM 008 C MS		T0054461799N	40	19.0	0.8	Conical Ø 0.8 mm, MIL-SPEC

GULLWING						
Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTM 020 G		T0054461099N	40	21.0	2.0/1.2	Gull Wing Ø 1.2 x 2.0 mm
RTM 020 G MS		T0054462499N	40	21.0	2.0/1.2	Gull Wing Ø 1.2 x 2.0 mm, MIL-SPEC

KNIFE						
Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTM 025 K		T0050101199	40	19.0	2.5/0.3	Knife 2.5 mm
RTM 025 K MS		T0050101299	40	19.0	2.5/0.3	Knife 2.5 mm, MIL-SPEC
RTM 030 K		T0054460799N	40	20.0	3.0	Knife tip 45° sloped 2.2 mm
RTM 030 K MS		T0054462199N	40	20.0	3.0	Knife tip 2.2 mm, MIL-SPEC

MEASURING TIP						
Model		Order No.	Watt	Length (mm)	a/b (mm)	Description
RTM Measuring tip		T0054461399N	40	26		RT Measuring tip for WXMP / WMRP